




Superior
Manufacturing
Group, Inc.

V-Groove Corrugated Runners™ (730 - Vinyl/750 - Rubber)

Industrial & Commercial Runners



Available Colors: Black

Good Better Best Superior



Available in both vinyl or rubber compounds, the V-Groove Corrugated Runners™ feature a rib-tooth design to improve traction. They also create a barrier to cold flooring substrates, and create a silencing effect over noisy tile. Corrugated V-Groove matting can also be used as a liner for maintenance and tool carts.

Test	Test Description	*Results
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	N/A
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	(730) .71 (750) .73
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	(730) 5.66 Grams (750) 5.89 Grams
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in weight needed to break, and % of size increase at breaking point.	(730) 150% (750) (data currently unavailable)
Hardness ASTM D2240-02	The hardness of a test sample is measured by means of a type A Shore Durometer. It measures the penetration of its specified indenter forced into the material under specified conditions	(730) 88 (750) (data currently unavailable)

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

- Available in two versions:
 - The #730 utilizes a vinyl compound
 - The #750 utilizes a rubber compound
- Thickness: 1/8"
- Weight: .80 lbs/sq. ft.
- Stock Sizes: (Rolls)
 - 730: 2' x 105', 3' x 105', 4' x 105'
 - 750: 2' x 150', 3' x 150', 4' x 150', 2' x 75', 3' x 75', 4' x 75', 6' x 75'
- Custom sizes available in 2', 3', and 4' widths (730), and 2', 3', 4', and 6' widths (750)
- Temperature Range: -20° F to +160° F
- Motor Vehicle Safety Standard #302 (Flame Test) - Pass



Anti-Slip



Custom Lengths



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NoTRAX® INDUSTRIAL MATS