



**Specification**

Product name: Self-Closing Non-Expandable Wrap

Material: Polyester

Working temperature: -40°C ~ +125°C

Melting point: 240±10°C

Flammability: Test piece conforms to class V0 per UL94

Abrasion resistance: Scratches times ≥ 2000 per ISO6722-1

Overlap: 50%

Certificate: RoHS

Version	Modification content	Reviser	Date
A2	Revised table, added symbols ☆ of characteristics	E H	2019-4-30
A3	ID is canceled, bundle range is revised.	L B	2019-9-26
A4	Thickness is added.	G Y	2022-3-9

Part No.	Spread width ☆ (mm)	Max. bundle dia. (mm)	Wall thickness mm	Nominal Size (in)
AUTO-WRAP-0125	28±4	3~5	0.6±0.15	1/8
AUTO-WRAP-025	38±4	6~8		1/4
AUTO-WRAP-0375	50±6	9~10		3/8
AUTO-WRAP-050	60±6	11~13		1/2
AUTO-WRAP-0625	80±6	14~16		5/8
AUTO-WRAP-075	100±10	17~19		3/4
AUTO-WRAP-100	120±10	23~25		1
AUTO-WRAP-1125	135±10	27~29		1.125
AUTO-WRAP-125	155±10	30~32		1.25
AUTO-WRAP-150	180±10	36~38		1.5
AUTO-WRAP-200	230±10	48~50		2

Manufacturer	<b>ELECTRIDUCT INC</b> 1650 NW 18th Street, Unit 801 Pompano Beach FL, 33069 Tel: 866-673-9590   sales@electriduct.com		
Specification No.	BS-J-SCW	Unit	mm
Product code	BS-J-SCW	Version	A4
REV.0		Special characteristics	☆ Represent key special characteristics
Prepared	G Y	Date	2022-3-9
Checked	T R	Date	2022-3-9
Approved	C B	Date	2022-3-9