

Specification

Product name: Fast Wrap

Material: Nylon+ waterproof

PU Hook/Loopmaterial: Nylon

Working temperature: -40°C ~ +125°C

Melting point: 220±10°C

☆Abrasion property: Refer to ISO6722-1 test method (N≥100 thousands times)

☆Waterproof property: Conduct water test according to GB/T 4745-2012, conform to level 3-4.


Color: Black

Application: It is widely used in the industry of mechanical, wind power generation, electron, etc., it can protect and beautify the cables, with excellent waterproof, dust-proof and abrasion properties.

Cutting tools: Hot knife, scissors

Certificate: RoHS

Nominal Size	ID (mm)	Width (W)	Thickness (T)	
1"	25.4±3	100±9mm	0.75±0.1mm	
1.5"	38±3	140±9mm	0.75±0.1mm	
2"	50.8±3	198±9mm	0.75±0.1mm	
2.5"	63.5±3	238±9mm	0.75±0.1mm	
3"	76.2±3	278±9mm	0.75±0.1mm	
3.5"	88.9±3	318±9mm	0.75±0.1mm	
4"	101.6±3	357±9mm	0.75±0.1mm	
4.5"	114.3±3	397±9mm	0.75±0.1mm	
5"	127±3	437±9mm	0.75±0.1mm	
6"	152.4±3	517±9mm	0.75±0.1mm	
7"	177.8±3	597±9mm	0.75±0.1mm	
8"	203.2±3	676±9mm	0.75±0.1mm	
9"	228.6±3	756±9mm	0.75±0.1mm	
10"	254±3	836±9mm	0.75±0.1mm	
11"	279.4±3	915±9mm	0.75±0.1mm	
12"	304.8±3	996±9mm	0.75±0.1mm	
13"	330.2±3	1075±9mm	0.75±0.1mm	
14"	355.6±3	1155±9mm	0.75±0.1mm	
15"	381±3	1234±9mm	0.75±0.1mm	
16"	406.43	1314±9mm	0.75±0.1mm	

ELECTRIDUCT INC			
Manufacturer	ADD: 1650 NW 18th Street, Unit: 801 CITY: Pompano Beach, Florida, 33069 Tel: 866-673-9590 Website: sales@electriduct.com		
Specification No.	FASTWRAP	Unit	mm
Product code	BS- J-FASTWRAP	Version	A1
REV.0		Special characteristics	☆ Represent key special characteristics
Prepared	P J	Date	2019-10-15
Checked	T S	Date	2019-10-15
Approved	N L	Date	2019-10-15