

Specification:

Product name: Hook Self-Closing Braided Wrap

Material:PET

Melt point:240±10℃

Working temperature:-40℃~ +125℃

Cold resistance:after testing at -40℃ for 4H, no signs of rupture and degradation.

Short term aging: after testing at 158℃ for 168H,no signs of rupture and degradation.

Flammability:refers to UL94, conforms to V-2 grade.



Abrasion:refers to ISO6722-1, abrasion > 1000 times.

Cutting tool:hot knife

Certificate:RoHS

Version	Modification content	Reviser	Date

P/N	Nominal ID (mm)	Max.function ID (mm)	Nominal Size (in)
BS-J-SCW-0125	3	3.5	1/8
BS-J-SCW-025	6	7.0	1/4
BS-J-SCW-0375	10	11.0	3/8
BS-J-SCW-050	13	14.0	1/2
BS-J-SCW-0625	16	17.0	5/8
BS-J-SCW-075	19	21.0	3/4
BS-J-SCW-100	25	27.0	1
BS-J-SCW-1125	29	30.0	1.125
BS-J-SCW-125	32	33.0	1.25
BS-J-SCW-150	38	40.0	1.5
BS-J-SCW-200	50	50.0	2

Manufacturer	ELECTRIDUCT INC		
	1650 NW 18th Street, Unit 801 Pompano Beach FL, 33069 Tel: 866-673-9590 sales@electriduct.com		
Drawing no.	BS-J-SCW	Unit	mm
Product code	BS-J-SCW	Version	A1
REV.0	 	SC symbol	☆ Represent the special key SC
Prepared	B L	Date	Sep 19, 2020
Checked	T R	Date	Sep 19, 2020
Approved	A D	Date	Sep 19, 2020