



DATE	REV	DESCRIPTION	BY	CHKD



Marking: YFC CAT.6 UTP ISO/IEC 11801 & EN 50288 & TIA/EIA-568-B.2-1 ETL/3P VERIFIED - 24AWGX4P
 PATCH TYPE CM (UL) C(UL) CMH E164469-F3




orange 1	green 2
white/orange	white/green
blue 3	brown 4
white/blue	white/brown

PA/R	PINOUT		
	P1 (T568B)	WIRE	P2 (T568B)
1	1	WHT/ORG	1
	2	ORG	2
2	3	WHT/GRN	3
	6	GRN	6
3	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8

Conductor	Bare Copper 24AWG 7/0.196±0.015mm
Insulation	Thickness:MIN at any point:0.15mm MAX AVG:0.25mm Diameter:1.04±0.06mm
Jacketing PVC	Thickness:MIN at any point:0.46mm MAX AVG:0.58mm Diameter:5.9±0.15mm


WIRE	CAT6 UTP STR 24AWG
PLUG	YUS-04
Length	× × M
WIRE COLOR	×



Unless specified on the drawing, tolerances are per the follows:

.	± 1
.X	± 0.2
.XX	± 0.05

3RD



DRAW.NO	YUS-04	ITEM	CAT.6 UTP 24AWG*4P	
DEPARTMENT		DRAW	SWH	DATE 2006/08/29
SCALE		CHECKER		APPROVAL
UNIT	MM	SHEET	1	OF 1