



| Version | Modification Content | Reviser | Date |
|---------|----------------------|---------|------|
| | | | |
| | | | |

Product name: 4:1 Adhesive Lined Heat Shrink Tube

Material: Polyethylene

☆ Working temperature: -55 °C ~ + 125 °C

Shrinking temperature: ≥125 °C

Vertical shrinkage ratio: ± 10% Shrink ratio: 4: 1

☆ Flame retardant grade: VW-1

Tools: hot air gun, tunnel furnace

Features: Heat-shrinkable tubing provides insulation protection for wires, cables, and wire terminals. It has high-temperature shrinkage, soft flame retardancy, insulation, corrosion protection, and is widely used in the insulation of various wire harnesses, solder joints, and inductors.

☆ Protection and anti-rust, anti-corrosion of metal pipes and rods.

☆ Certification: RoHS

| Product number | Before shrinking (mm) | | After shrinking (mm) | | |
|----------------|-----------------------|--------------------------|----------------------|------------------|-----------|
| | ID. D | Average wall thickness H | Inside diameter d | Wall thickness h | Adhesive |
| HS4-DW-016 | 4.50±0.50 | 0.50±0.20 | 1.00 | 1.00±0.20 | 0.40±0.15 |
| HS4-DW-025 | 6.50±0.50 | 0.50±0.20 | 1.50 | 1.10±0.20 | 0.50±0.20 |
| HS4-DW-032 | 8.50±0.50 | 0.70±0.20 | 2.00 | 1.50±0.30 | 0.50±0.20 |
| HS4-DW-050 | 13.0±1.00 | 0.90±0.30 | 3.00 | 1.70±0.30 | 0.60±0.20 |
| HS4-DW-064 | 17.0±1.00 | 1.00±0.30 | 4.00 | 2.00±0.30 | 0.70±0.30 |
| HS4-DW-100 | 25.0±1.00 | 1.00±0.30 | 6.00 | 2.50±0.40 | 0.90±0.30 |
| HS4-DW-125 | 33.0±1.00 | 1.20±0.30 | 8.00 | 3.00±0.60 | 1.00±0.30 |
| HS4-DW-200 | 54.0±2.00 | 1.20±0.30 | 13.0 | 3.00±0.60 | 1.00±0.30 |

| | | | |
|------------------|---|-------------------------------|---|
| Manufacturer | ELECTRIDUCT INC | | |
| | ADD:1650 NW 18th Street, Unit 801 Pompano Beach Florida, 33069 | | |
| | Tel: 866-673-9590 Emal: sales@electriduct.com | | |
| Specification No | HS4-DW | unit | mm |
| Product Code | HS4-DW | version | A1 |
| REV.0 | | Special characteristic symbol | ☆ Represents important key special characteristics |
| Prepared | W. Y. | date | 2020-06-10 |
| Checked | D. L. | date | 2020-06-10 |
| Approved | Taj | date | 2020-06-10 |