

CAT5 ENHANCED 350MHz UTP PLENUM (CMP)



DESCRIPTION

Category-5E, 24AWG, UTP, 8C Solid Bare Copper, 350MHz, CMP Rated 1000ft.

FEATURES

- High-Performance Data Cable
- Suitable for High-Speed Applications
- Easily Identified Color-Striped Pairs
- Unshielded Twisted Pair (UTP) Cable
- 24AWG Solid Bare Copper Conductors
- Exceeds ANSI/TIA 568-B.2
- Excellent Attenuation and Crosstalk
- Plenum Rated , CMP
- UL, ETL Verified



Dimensions 14H x 14L x 9W (inches)
45pcs per pallet
(Packaging may vary)

SKU: 056 SERIES

Conductor	Solid Bare Copper
AWG	24
Insulation	FEP
Thickness	0.20mm
Jacket	FR-PVC
Outer Diameter	5.3mm
Rip Cord	Yes

Color of Pairs

Pair 1	Blue, White-Blue
Pair 2	Orange, White-Orange
Pair 3	Green, White-Green
Pair 4	Brown, White-Brown

Jacket Printing

Vertical Cable E191267 (UL) c(UL) 4PR 24AWG CMP FT6 - ETL CAT5E VERIFIED to TIA/EIA 568-B.2 ROHS COMPLIANT V1395P8383 1000FT

Electrical Characteristics

ANSI/TIA 568-B.2
Impedance :100Ω±15%

Standards

UL, cUL (E191267)
ETL Verified to ANSI/TIA 568-B.2 Category 5e

Applications

ANSI X3T9.5 TP-PMD (FDDI)
ATM PMD 155 Mbps
IEEE 802.3 Fast Ethernet :10 Base-T,
100 Base-T4, 100 Base-X
IEEE 802.5 :4/16 Mbps Token Ring
IEEE 802.12 :100 Base-VG

Jacket color available in
Blue, Green, Gray, Red, White, Yellow

VERTICAL CABLE

954 454-3554 Florida Office
951 696-7772 California Office



Intertek

www.verticalcable.com

Rev. 12/2011

Subject to change without notice.