



**Specification:**

Product name: WL-ED-UV  
 Material: polyamides (PA6)  
 ☆Working temperature: -40°C-- +125°C normal use  
 ☆Flammability: Flame resistance  
 Uv protection: GB/T 16422.3  
 Feature: highly flexible, light weight, easy to be installed, good abrasion resistance, excellent chemical resistance  
 Type: black tube, split or non-split, other color upon special orders  
 Application: It is Widely used in mechanical engineering, shipbuilding 、 electronics industry etc .  
 Approval: RoHS



No.	Modification content	Reviser	Date

Nom Size	I.D. (mm)	O.D. (mm)	Wall thickness(T) mm	W (mm)	L (mm)	Packing (M/Roll)
1/4"	5.5±0.3	8.5±0.3	0.25±0.3	1.75±0.3	2.6±0.3	100
10mm	7±0.3	10±0.3	0.27±0.05	2.0±0.2	2.9±0.2	100
3/8"	8.5±0.3	11.0±0.3	0.27±0.05	1.8±0.2	2.8±0.2	100
11.5mm	8.5±0.3	11.5±0.3	0.3±0.05	1.8±0.2	2.8±0.2	100
13mm	10±0.3	13±0.3	0.3±0.05	1.9±0.2	2.8±0.2	100
1/2"	12±0.4	15.8±0.4	0.3±0.05	2.2±0.2	3.3±0.2	100
18.5mm	14.3±0.4	18.5±0.4	0.32±0.05	2.6±0.2	3.6±0.2	100
3/4"	17.0±0.4	21.2±0.4	0.32±0.05	2.4±0.2	3.3±0.2	100
25mm	21±0.4	25±0.5	0.35±0.05	2.3±0.2	3.4±0.2	100
1"	23±0.5	28.5±0.5	0.35±0.05	2.3±0.2	3.3±0.2	50
1.25"	29±0.5	34.5±0.5	0.40±0.05	2.4±0.2	3.4±0.2	50
1.5"	36±0.5	42.5±0.5	0.45±0.05	2.9±0.2	4.3±0.2	25
2"	48±0.5	54.5±0.5	0.5±0.05	3.0±0.2	4.3±0.2	25

Manufacturer			<b>Electriduct Inc.</b>	
	Tel: 866-673-9590 ADD: 1650 NW 18th Street. Unit: 801 Pompano Beach Fl, 33069		Fax: 954-206-0799	
Specification No.	ELECT19-0031	Unit	mm	
Product code	WL-ED-UV	Version	A1	
REV.0		Special characteristics	☆Represent key special characteristics	
Prepared by	Q Y	Date	2019-01-22	
Checked by	J P	Date	2019-01-22	
Approved by	B Z	Date	2019-01-22	