



Product Name: HDPE Spiral Protector  
 Material: High Density Polyethylene (HDPE)  
 Product appearance: spiral shape, flat surface  
 Working temperature: -50°C~+100°C  
 Tensile strength: 25 Mpa at room temperature  
 Other characteristics: Wear resistance, oil resistance, ultraviolet light resistance  
 Certification: RoHS

Version	Modification content	Reviser	Date

P/N	OD mm	ID mm	WT W /mm	Screw pitch P/ mm
WL-SW-HD-0375	10.0±1	7.8±1	1.2±0.15	9.5±1
WL-SW-HD-050	12.0±1	9.6±1	1.20±0.15	10.5±1
WL-SW-HD-064	16.0±1	13.4±1	1.30±0.15	12±1
WL-SW-HD-075	20.0±1	16.0±1	2.00±0.15	20±1
WL-SW-HD-100	25.0±2	20.6±2	2.20±0.15	21.5±1
WL-SW-HD-1125	28.0±2	22.2±2	2.35±0.15	22±1
WL-SW-HD-125	32.0±2	27.0±2	2.50±0.25	22±1
WL-SW-HD-1375	38.0±2	32.2±2	2.65±0.25	23±1
WL-SW-HD-150	40.0±2	34.6±2	2.70±0.30	24±1
WL-SW-HD-200	48.5±3	41.5±3	3.40±0.30	30±1
WL-SW-HD-250	62.6±3	56.0±3	3.70±0.30	37±2
WL-SW-HD-300	75.0±4	66.2±4	4.40±0.40	42±2
WL-SW-HD-350	90.0±5	80.2±5	4.80±0.40	45±2
WL-SW-HD-440	110±6	99.0±6	5.20±0.40	50±3
WL-SW-HD-500	125±6	113.2±6	5.50±0.40	52±3

Manufacturer	<b>ELECTRIDUCT INC</b> 1650 NW 18th Street, Unit 801 Pompano Beach FL, 33069 Tel: 866-673-9590   sales@electriduct.com		
Drawing No.	WL-SW-HD	Unit	mm
Product code	WL-SW-HD	Version	A2
REV.0		SC symbol	☆ Represent the special key SC
Prepared	L C Q	Date	2022-2-22
Checked	J P	Date	2022-2-22
Approved	M P	Date	2022-2-22